

AD-A051 590

FOREIGN TECHNOLOGY DIV WRIGHT-PATTERSON AFB OHIO
SPECTRAL ANALYSIS OF THE ENVELOPE OF AN AMPLITUDE-MODULATED SIG--ETC(U)
SEP 77 A A VORONIN, A G GORDIYENKO
FTD-ID(RS)T-1678-77

F/G 9/5

UNCLASSIFIED

NL

| OF |
AD
A051 590



END

DATE
FILMED

4-78

DDC

FOREIGN TECHNOLOGY DIVISION




①

SPECTRAL ANALYSIS OF THE ENVELOPE OF AN AMPLITUDE-MODULATED SIGNAL AT THE OUTPUT OF AN AMPLIFIER WITH A LOGARITHMIC AMPLITUDE CHARACTERISTIC

by

A. A. Voronin and A. G. Gordiyenko



Approved for public release;
distribution unlimited.

AD-A051590

EDITED TRANSLATION

FTD-ID(RS)T-1678-77

26 September 1977

MICROFICHE NR: *AD-77-C-001265*

SPECTRAL ANALYSIS OF THE ENVELOPE OF AN AMPLITUDE-MODULATED SIGNAL AT THE OUTPUT OF AN AMPLIFIER WITH A LOGARITHMIC AMPLITUDE CHARACTERISTIC

By: A. A. Voronin and A. G. Gordiyenko

English pages: 6

Source: Radiotekhnika, Khar'kov, Nr 21, 1972,
PP. 15-17

Country of origin: USSR

Translated by: Carol S. Nack

Requester: FTD/ETWR

Approved for public release; distribution unlimited

THIS TRANSLATION IS A RENDITION OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:

TRANSLATION DIVISION
FOREIGN TECHNOLOGY DIVISION
WP-AFB, OHIO.

FTD-ID(RS)T-1678-77

Date 26 Sep 19 77

U. S. BOARD ON GEOGRAPHIC NAMES TRANSLITERATION SYSTEM

Block	Italic	Transliteration	Block	Italic	Transliteration
А а	<i>А а</i>	A, a	Р р	<i>Р р</i>	R, r
Б б	<i>Б б</i>	B, b	С с	<i>С с</i>	S, s
В в	<i>В в</i>	V, v	Т т	<i>Т т</i>	T, t
Г г	<i>Г г</i>	G, g	У у	<i>У у</i>	U, u
Д д	<i>Д д</i>	D, d	Ф ф	<i>Ф ф</i>	F, f
Е е	<i>Е е</i>	Ye, ye; E, e*	Х х	<i>Х х</i>	Kh, kh
Ж ж	<i>Ж ж</i>	Zh, zh	Ц ц	<i>Ц ц</i>	Ts, ts
З з	<i>З з</i>	Z, z	Ч ч	<i>Ч ч</i>	Ch, ch
И и	<i>И и</i>	I, i	Ш ш	<i>Ш ш</i>	Sh, sh
Й й	<i>Й й</i>	Y, y	Щ щ	<i>Щ щ</i>	Shch, shch
К к	<i>К к</i>	K, k	Ъ ъ	<i>Ъ ъ</i>	"
Л л	<i>Л л</i>	L, l	Ы ы	<i>Ы ы</i>	Y, y
М м	<i>М м</i>	M, m	Ь ь	<i>Ь ь</i>	'
Н н	<i>Н н</i>	N, n	Э э	<i>Э э</i>	E, e
О о	<i>О о</i>	O, o	Ю ю	<i>Ю ю</i>	Yu, yu
П п	<i>П п</i>	P, p	Я я	<i>Я я</i>	Ya, ya

*ye initially, after vowels, and after Ъ, Ь; e elsewhere.
 When written as ë in Russian, transliterate as yë or ë.
 The use of diacritical marks is preferred, but such marks may be omitted when expediency dictates.

GREEK ALPHABET

Alpha	A	α	α	Nu	N	ν
Beta	B	β		Xi	Ξ	ξ
Gamma	Γ	γ		Omicron	Ο	ο
Delta	Δ	δ		Pi	Π	π
Epsilon	E	ε	ε	Rho	Ρ	ρ ϑ
Zeta	Z	ζ		Sigma	Σ	σ ς
Eta	H	η		Tau	Τ	τ
Theta	Θ	θ	θ	Upsilon	Υ	υ
Iota	I	ι		Phi	Φ	φ ϕ
Kappa	K	κ	κ	Chi	Χ	χ
Lambda	Λ	λ		Psi	Ψ	ψ
Mu	M	μ		Omega	Ω	ω

RUSSIAN AND ENGLISH TRIGONOMETRIC FUNCTIONS

Russian	English
---------	---------

sin	sin
cos	cos
tg	tan
ctg	cot
sec	sec
cosec	csc
sh	sinh
ch	cosh
th	tanh
cth	coth
sch	sech
csch	csch
arc sin	\sin^{-1}
arc cos	\cos^{-1}
arc tg	\tan^{-1}
arc ctg	\cot^{-1}
arc sec	\sec^{-1}
arc cosec	\csc^{-1}
arc sh	\sinh^{-1}
arc ch	\cosh^{-1}
arc th	\tanh^{-1}
arc cth	\coth^{-1}
arc sch	sech^{-1}
arc csch	csch^{-1}

rot	curl
lg	log

GRAPHICS DISCLAIMER

All figures, graphics, tables, equations, etc. merged into this translation were extracted from the best quality copy available.

1678

SPECTRAL ANALYSIS OF THE ENVELOPE OF AN AMPLITUDE-MODULATED SIGNAL AT
THE OUTPUT OF AN AMPLIFIER WITH A LOGARITHMIC AMPLITUDE
CHARACTERISTIC

A. A. Voronin and A. G. Gordiyenko

Khar'kov

When AM oscillations pass through an amplifier with a logarithmic amplitude characteristic (LAC) [M.A.K.], nonlinear distortions which depend on the modulation coefficient (m) originate in the amplifier. Amplifiers with LAC are used extensively in different communication channels, measuring and other devices. In connection with this, it is necessary to estimate the coefficient of nonlinear distortions at the output of the amplifier as a function of

m. No matter how it is obtained, the LAC of an amplifier [1] can be described by the expression

$$U_{\text{out}} = k_0 U_{\text{in}} \left(a \ln \frac{U_{\text{out}}}{U_{\text{in}}} + 1 \right), \quad (1)$$

where U_{out} is the output voltage of the amplifier; k_0 is the maximum gain of the amplifier (in the linear mode); U_{in} is the input voltage at which the LAC of the amplifier begins; a is the coefficient which determines the dynamic range of the amplifier according to the output voltage; and U_{in} is the voltage at the input of the amplifier.

We will assume that the input signal is modulated by one frequency. Substituting the value of U_{in} in expression (1), we will have

$$U_{\text{out}} = k_0 U_{\text{in}} \left[a \ln \frac{U_{\text{out}}}{U_{\text{in}}} + a \ln (1 + m \cos x) + 1 \right], \quad (2)$$

where U_{in} is the level of the carrier signal at the amplifier input.

Obviously, the spectrum of the envelope is determined by the expression

$$\ln (1 + m \cos x). \quad (3)$$

In the case in question, the modulation coefficient is considered to be less than one ($m < 1$), whereupon the following

inequality is satisfied:

$$0 < \ln(1 + m \cos x) \leq 2, \quad (4)$$

In this case, expression (3) can be represented in the form of an exponential series [2] and, after transformation, we will have

$$\ln(1 + m \cos x) = A_0 + B_{1,n} \cos(2t-1)x + A_{t,n} \cos 2tx, \quad (5)$$

where

$$\begin{aligned} A_0 &= \sum_{n=1}^{\infty} (-1)^{2n+1} \frac{m^{2n}}{2n} \cdot \frac{1}{2^{2n-1}} \binom{2n}{n}; \\ B_{1,n} &= \sum_{n=1}^{\infty} (-1)^{2n} \frac{m^{2n-1}}{2n-1} \times \\ &\quad \times \frac{1}{2^{2n-2}} \binom{2n-1}{n-1}; \\ A_{t,n} &= \sum_{n=1}^{\infty} (-1)^{2n+1} \frac{m^{2n}}{2n} \times \\ &\quad \times \frac{1}{2^{2n-1}} \binom{2n}{n-t}. \end{aligned}$$

If we designate $k_0 U_{\text{out}} = d$ (d is the amplifier parameter), expression (1) assumes the form

$$\begin{aligned} U_{\text{out}} &= d \left(a \ln \frac{U_{\text{in}}}{U_{\text{out}}} + aA_0 + 1 \right) + \\ &\quad + adB_{1,n} \cos(2t-1)x + \\ &\quad + adA_{t,n} \cos 2tx, \quad (6) \end{aligned}$$

where $d \left(a \ln \frac{U_{\text{in}}}{U_{\text{out}}} + aA_0 + 1 \right)$ is the carrier level at the amplifier output during amplitude modulation; $adA_{t,n}$ is the amplitude of the even harmonics in the spectrum of the signal envelope at the amplifier output; $adB_{1,n}$ is the amplitude of the odd harmonics in

the spectrum of the signal envelope at the amplifier output.

Analyzing the results obtained from the theoretical calculation, we can conclude that the carrier level at the output of amplifiers with LAC depends on the level and coefficient of modulation of the signal at the amplifier input, while the level of the envelope at the amplifier output only depends on the modulation coefficient of the input signal.

The verification agreed well with the experimental data and the results of the theoretical calculation.

Calculated by computer depending on the modulation coefficient, values A_0 , $A_{1,n}$ and $B_{1,n}$ are proportional with respect to the first component and are represented by curves in the figure.


The curves obtained make it possible to find the harmonic coefficient in amplifiers with LAC at different modulation coefficients, as well as to solve the reverse problem: given the nonlinear distortion coefficient, we can find the permissible modulation coefficient. The curves are also used in analyzing measurement results.

Bibliography

1. V. M. Volkov. Logarithmic Amplifiers. Gostekhizdat UkrSSR, Kiev, 1962.

2. I. S. Gradshteyn, I. M. Ryzhik. Tables of Integrals, Sums, Series, and Derivatives. Fizmatgiz, 1963.

Figure. Normalized values of coefficients which determine the level of the spectral components ($B_{1,n}$ is the coefficient which determines the level of the first harmonic).



UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

REPORT DOCUMENTATION PAGE		READ INSTRUCTIONS BEFORE COMPLETING FORM																		
1. REPORT NUMBER FTD-ID(RS)T-1678-77	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER																		
4. TITLE (and Subtitle) SPECTRAL ANALYSIS OF THE ENVELOPE OF AN AMPLITUDE-MODULATED SIGNAL AT THE OUTPUT OF AN AMPLIFIER WITH A LOGARITHMIC AMPLITUDE CHARACTERISTIC		5. TYPE OF REPORT & PERIOD COVERED Translation																		
		6. PERFORMING ORG. REPORT NUMBER																		
7. AUTHOR(s) A. A. Voronin and A. G. Gordiyenko		8. CONTRACT OR GRANT NUMBER(s)																		
9. PERFORMING ORGANIZATION NAME AND ADDRESS Foreign Technology Division Air Force Systems Command U. S. Air Force		10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS																		
11. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE 1972																		
		13. NUMBER OF PAGES 6																		
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)		15. SECURITY CLASS. (of this report) UNCLASSIFIED																		
		15a. DECLASSIFICATION/DOWNGRADING SCHEDULE																		
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release: distribution unlimited.																				
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)																				
18. SUPPLEMENTARY NOTES		<table border="1"><tr><td colspan="2">ACCESSION for</td></tr><tr><td>NTIS</td><td>White Section <input checked="" type="checkbox"/></td></tr><tr><td>DOC</td><td>Buff Section <input type="checkbox"/></td></tr><tr><td>UNANNOUNCED</td><td><input type="checkbox"/></td></tr><tr><td colspan="2">JUSTIFICATION.....</td></tr><tr><td colspan="2">BY.....</td></tr><tr><td colspan="2">DISTRIBUTION/AVAILABILITY CODES</td></tr><tr><td>Dist.</td><td>AVAIL. and/or SPECIAL</td></tr><tr><td>A</td><td></td></tr></table>	ACCESSION for		NTIS	White Section <input checked="" type="checkbox"/>	DOC	Buff Section <input type="checkbox"/>	UNANNOUNCED	<input type="checkbox"/>	JUSTIFICATION.....		BY.....		DISTRIBUTION/AVAILABILITY CODES		Dist.	AVAIL. and/or SPECIAL	A	
ACCESSION for																				
NTIS	White Section <input checked="" type="checkbox"/>																			
DOC	Buff Section <input type="checkbox"/>																			
UNANNOUNCED	<input type="checkbox"/>																			
JUSTIFICATION.....																				
BY.....																				
DISTRIBUTION/AVAILABILITY CODES																				
Dist.	AVAIL. and/or SPECIAL																			
A																				
19. KEY WORDS (Continue on reverse side if necessary and identify by block number)																				
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) 09;17																				

DD FORM 1 JAN 73 1473

EDITION OF 1 NOV 65 IS OBSOLETE

UNCLASSIFIED

SECURITY CLASSIFICATION OF THIS PAGE (When Data Entered)

DISTRIBUTION LIST

DISTRIBUTION DIRECT TO RECIPIENT

ORGANIZATION	MICROFICHE	ORGANIZATION	MICROFICHE
A205 DMATC	1	E053 AF/INAKA	1
A210 DMAAC	2	E017 AF/RDXTR-W	1
B344 DIA/RDS-3C	8	E404 AEDC	1
C043 USAMIIA	1	E408 AFWL	1
C509 BALLISTIC RES LABS	1	E410 ADTC	1
C510 AIR MOBILITY R&D	1	E413 ESD	2
LAB/FIO		FTD	
C513 PICATINNY ARSENAL	1	CCN	1
C535 AVIATION SYS COMD	1	ETID	3
C557 USAIIC	1	NIA/PHS	1
C591 FSTC	5	NICD	5
C619 MIA REDSTONE	1		
D008 NISC	1		
H300 USAICE (USAREUR)	1		
P005 ERDA	1		
P055 CIA/CRS/ADD/SD	1		
NAVORDSTA (50L)	1		
NASA/KSI	1		
AFIT/LD	1		

FTD-ID(RS)T-1678-77